

#### Synapse Bootcamp Module 14 Modeling Data Manually

v0.4 - May 2024

## Objectives

- Discuss use cases for creating nodes manually
- Understand how to map real-world data and information into Synapse's data model
- Gain familiarity with some forms that may require manual modeling
- Describe how you can use Synapse to represent strategic data



## **Modeling Data Manually**

#### $\checkmark$

# **Modeling Manually**

- Capture information that cannot be ingested automatically
- May include:
  - One-off indicators or information
  - Unstructured or badly-formatted data
  - Non-traditional indicators
- Often records:
  - Supporting evidence
  - Strategic data
- Capture more abstract or complex concepts
  - Classes or categories (ou:industry)
  - Objectives (ou:goal, ou:campaign)
  - Attacks or compromises (risk:attack, risk:compromise)



#### **Common 'One-Off' Data**

Form	Object	Purpose
ou:org	Company, government ministry, group	Represent a real organized entity
ps:contact	A collection of data associated with a purported individual or organization	Capture identifying data for entity resolution
ps:person	A known person	Represent a real individual
media:news	Article, blog, whitepaper, report	Source for other data (indicators, victims, real world events)



## Common 'One-Off' Data

Form	Object	Purpose
inet:service:account inet:web:acct	User or group account (e.g., social media, forum user, etc.)	Account owned by threat actor Account used maliciously
inet:service:message inet:web:post	Message posted to a service	Social media post, forum post
inet:service:message inet:web:mesg	Private message between accounts	Social media phishing, threat actor communications
tel:txtmesg	Mobile device message (SMS, iMessage)	Smishing, threat actor communications

inet:service:\* forms were introduced in June 2024 and will replace inet:web:\* forms.

## **Node Deconfliction**

- Many nodes we create manually are guid nodes
  - Easily create an arbitrary guid using '\*'
  - o [ ou:org=\* :name='the vertex project' ]
- Problem: how to avoid duplicate nodes?
  - Two users create two different **arbitrary** ou : org nodes for The Vertex Project
- Solution: check whether the node already exists
  - Use a "meaningful" secondary property
  - ou:org:name='the vertex project'
  - ou:name='the vertex project' -> ou:org
  - Use Lookup mode to search (e.g., 'vertex')

#### **Manually** checking for duplicates works...but is an imperfect solution.



## Storm gen.\* Commands

- Storm gen.\* ("generate") commands can deconflict for you!
- Commands for many common guid forms
  - Orgs, threats, vulnerabilities...
- Takes property value(s) as input
- Checks for an existing node, based on the value
  - **Lifts** (returns) the existing node if found
  - **Creates** (generates) a new node (based on the provided value(s)) if not

gen.ou.org 'the vertex project'



## Modeling Data Demo



## Strategic Data

© 2024 The Vertex Project, LLC



## **Strategic Data**

- Synapse can represent a broad range of data
- Much of this data is tactical
  - Atomic indicators or objects
    - Files, URLs, organizations
  - Concrete observables or relationships
    - A file connected to an IP, a domain was registered through a specific company
- Strategic analysis commonly done "the long way"
  - Review and consolidate multiple reports
  - Write another report



## **Strategic Data**

- Synapse allows you to:
  - Record more abstract concepts ('goals')
  - Represent concise data for events ('attacks', 'compromises')
  - Link events to concrete indicators
  - Link events to their objectives
- Structurally representing things like:
  - IOCs linked to...
  - ...individual attacks that are part of...
  - ...specific compromises meant to achieve...
  - ...particular objectives
- ...allows you to **answer questions** about strategic data as well

Many "strategic" forms are used for Synapse's threat intel data model.



## Sample Strategic Forms

Events		Objectives	
Form	Purpose	Form	Purpose
risk:attack	Specific / atomic malicious event	ou:goal	Objective (broad or tactical)
risk:attacktype	User-defined set of categories	ou:camptype	User-defined set of categories
risk:compromise	Broader event; comprised of one or more attacks	ou:campaign	Broad objective; comprised of one or more goals

These are not mutually exclusive - for example, attacks can have goals and be part of campaigns.



#### risk:attack

Category	Questions	Model Element
Who	Who/what was attacked (host, location)? Who carried out the attack? Who is reporting on the attack?	-(targets)> :attacker / #rep.mandiant.apt41 :reporter:name / :reporter
What	What kind of attack was this? Was the attack targeted? Was the attack successful? Was the attack part of a larger compromise? A broader campaign?	:type :targeted :success :compromise, :campaign
When	When did the attack occur? When was it detected?	:time :detected
Why	What was the purpose of the attack?	:goal
How	What did the attacker use to carry out the attack? How sophisticated was the attack? How bad was any impact from the attack?	-(uses)> :sophistication :severity



## risk:compromise

Category	Questions	Properties
Who	Who/what was the target/victim? Who was the perpetrator? Who is reporting on the compromise?	:target :attacker / #rep.mandiant.apt41 :reporter:name / :reporter
What	What kind of compromise was this? Was the compromise part of a broader campaign?	:type :campaign
When	When did the compromise start? End? How long did the compromise last?	:time / :lasttime :duration
Why	What was the purpose of the compromise?	:goal :goals
How	How did the compromise impact the victim? How did the attacker carry out the compromise? How significant was the impact of the compromise?	:loss:* / :ransom:* / :theft:* / :response:cost -(uses)> :severity



## Modeling Strategic Data - Demo

#### Summary

- There are many cases where you will need to manually model data
  - **One-off** objects or occurrences
  - Non-standard or less common indicators
  - Capturing supporting evidence
  - Representing more strategic or abstract information
- Modeling entails:
  - Identify the appropriate form to use
  - Map real-world data to the form **properties**